

Bedside Infotainment Terminal

BIS-W19C-ULT4 | 18.5" Medical Panel PC with 7th Generation Intel® mobile ULT Core™ i5/Celeron® processor

Features

- 18.5" 16:9 LED panel (1366 x 768 / 1920 x 1080)
- 7th generation Intel® Core™ i5-7300U and Celeron® 3865 CPU
- Projected capacitive touchscreen supports multi-touch
- IP65 compliant front bezel
- Anti-bacteria cover
- HDMI input supported (monitor mode)
- Optional 3-in-1 card reader: MSR, SCR and fingerprint
- Optional Mifare RFID module
- Optional VoIP phone handset
- Optional handle module with barcode scanner and reading light



» Monitor Mode Application

Dual System Redundancy

Embedded System

Wireless Video/Audio

Airplay
Miracast / DLNA
HDMI Dongle

Small screen to the big screen

Smartphone/
iPAD / iPhone

HDMI Source

For HDMI input function, we put a physical on the bottom to make the mode switching process more smoothly and friendly.

PC mode

Monitor mode

- Wireless TX/RX Module
- HDMI input/output
- EMR Carrier
- Operation Room Teaching & Observation

» Applications



● Push notification services for patients

Inpatients may need health education from hospital or reading the preoperative notice before surgery. The BIS-W19C-ULT3 could be integrated with the hospital server to realize these functions, with which most of the action of health education could be digitized to reduce human resources.



● HIS/NIS system for nurses

Most of the hospitals make use of digital information system to avoid human error and to optimize caring flow. The BIS-W19C-ULT3 could be integrated with the HIS/NIS system, from which clinicians can easily check doctors' prescriptions and record patients' vital information to the data center directly.



● Entertainment for patients

Inpatients in the hospital may have plenty of time except consultation of doctors or doing a surgery, which means inpatients also need some entertainments. The BIS-W19C-ULT3 could be integrated with the bedside software applications which aggregate various functions that inpatients may need. The bedside solution could offer inpatients all the daily requirements.



● Patient counseling discussion

Ward rounds are a major daily work of doctors. It is difficult for the doctor to carry all patients' medical information during ward rounds. The generation of digital healthcare is happening. The doctor can just bring a tablet during ward rounds to explain all the medical conditions to each inpatient. Wireless video streaming to a bigger screen helps doctors, inpatients and family members have a more convenient discussing environment.

Specifications

Model		BIS-W19C-ULT4
LCD Specifications	LCD Display	18.5" (16:9)
	Max Resolution	1366 (W) x 768 (H) / 1920 (W) x 1080 (H)
	Brightness (cd/m ²)	250 / 350
	Contrast Ratio	1000:1
	LCD Color	16.7M colors (RGB 6-bit) / 16.7M colors (RGB true 8-bit)
	Pixel Pitch (mm)	0.3 (H) x 0.3 (V) / 0.213 (H) x 0.213 (V)
	Viewing Angle (H-V)	170°(H) / 160°(V), 178°(H) / 178°(V)
	Backlight MTBF (hrs)	30000 (LED backlight) / 50000 (LED backlight)
Touch	Touchscreen	Projected capacitive type with USB interface
	Surface Hardness	6H
System	CPU Support	Intel® Kabylake ULT platform Core™ i5-7300U and Celeron® 3865U
	RAM	Two 260-pin 2133/1866 MHz dual-channel DDR4 non-ECC unbuffered SO-DIMMs (system max. 32GB)
	I/O Port	<p>Rear</p> <ul style="list-style-type: none"> 1 x 1.5kV isolation COM port 1 x 12~28V DC Jack 1 x GbE LAN port 2 x USB 3.2 Gen 1 port <p>Bottom</p> <ul style="list-style-type: none"> 1 x RJ-11 for barcode scanner (1D/2D) 1 x GbE LAN port 2 x USB 3.2 Gen 1 port 1 x HDMI output <p>Side</p> <ul style="list-style-type: none"> 1 x HDMI input 2 x USB 2.0 port 1 x Audio out 1 x Mic in
	Storage	1 x 2.5" SATA 6Gb/s HDD/SDD bay 1 x mSATA (Reserved)
	Audio	2 x 2W speaker
	Webcam & Microphone	2-megapixel CMOS front-facing camera with auto-focus and digital microphone
	LED Indicator	RFID indicator LED
	Other Features	Monitor Mode
Function Key		<ul style="list-style-type: none"> 1 x LCD on/off 1 x Brightness up 1 x Brightness down 1 x Volume up 1 x Volume down 1 x Touch lock button for cleaning <p>Combinations:</p> <ul style="list-style-type: none"> 1 x Auto-dimming on/off
Light Sensor		Ambient light sensor for panel brightness adjustment
Cooling Method		Fan-less
Connectivity		Wi-Fi and Bluetooth
Physical	Construction Material	ABS+PC plastic with anti-bacterial material
	Mounting	Wall, Stand and Arm VESA 100/75
	Net Weight	6.5 kg
	Dimensions (WxHxD) (mm)	478.6 x 317.3 x 60.1
Environment	Operating Temperature	0°C~40°C
	Storage Temperature	-20°C~60°C
	Humidity	10% to 95% (non-condensing)
	Vibration	1G
	Shock	Operating Shock: 5G peak acceleration (11ms duration) Non-Operating Shock: 15G peak acceleration (11ms duration)
	IP Level	IP65 compliant front panel
Power	Power Input	12V~28V DC input
	Power Adapter	120W medical power adapter: Input: 100V~240V AC, Output: 19V DC

Ordering Information

Part No.	Description
BIS-W19CF-ULT4-C/PC/4G-R10	18.5" 350 cd/m ² 1920 x 1080 panel PC with 7th generation 14nm Intel® mobile Celeron® 3865U (15W) on-board processor (ULT), one 4GB DDR4 RAM, 802.11a/b/g/n/ac Wi-Fi module, PCAP touchscreen, 2-megapixel camera, microphone, R10
BIS-W19CF-ULT4-i5/PC/4G-R10	18.5" 350 cd/m ² 1920 x 1080 panel PC with 7th generation 14nm Intel® mobile Core™ i5-7300U (15W) on-board processor (ULT), one 4GB DDR4 RAM, 802.11a/b/g/n/ac Wi-Fi module, PCAP touchscreen, 2-megapixel camera, microphone, R10
BIS-W19C-ULT4-C/PC/4G-R10	18.5" 250 cd/m ² 1366 x 768 panel PC with 7th generation 14nm Intel® mobile Celeron® 3865U (15W) on-board processor (ULT), one 4GB DDR4 RAM, 802.11a/b/g/n/ac Wi-Fi module, PCAP touchscreen, 2-megapixel camera, microphone, R10
BIS-W19C-ULT4-i5/PC/4G-R10	18.5" 250 cd/m ² 1366 x 768 panel PC with 7th generation 14nm Intel® mobile Core™ i5-7300U (15W) on-board processor (ULT), one 4GB DDR4 RAM, 802.11a/b/g/n/ac Wi-Fi module, PCAP touchscreen, 2-megapixel camera, microphone, R10

Options

Part No.	Description
MEDP-HS-R10	USB interface VoIP phone and its holder, white
MEDP-CR-02-R10	Magnetic card reader/Smart card reader/Fingerprint sensor, white
MEDP-HD-R10	Metal handle covered with soft rubber
MEDP-HD-BR-R11	Metal handle covered with soft rubber, with barcode reader and reading light, White
MEDP-TPM-04-R10	Trusted platform module kit with 300mm cable, IEL assembly only
MEDP-EZS-R10	VESA 100 x 100 mm panel PC stand with a cable management hole, white
BIS-W19C-ULT4-W10E64-V-R10	OS Image with Windows Embedded Standard 10 E Value 64-bit for BIS-W19C, with DVD-ROM, RoHS
POCP-CC04-R10	BIS-19C-ULT4 cable cover, white, plastic, R10

IQ Mounting Options

Item	Part No.
Wall Mount Kit	AFLWK-19B
Arm	ARM-31-RS
Stand	STAND-A21-R10

Packing List

Item	Q'ty	Remark
Power Adapter	1	120W medical power adapter: Input: 90V~264V AC, Output: 19 V DC
Power Cord	1	European power cords, 183 CM, C13

I/O Interface

