

Heavy Industrial RS-232 to RS-422/485 Isolated Converter

Model BB-485DRCI-PH

ADVANTECH

www.advantech.com



PRODUCT FEATURES

- Converts RS-232 data signals to RS-422/RS-485
- 2kV 3-way isolation (input/output/power)
- Data rate: 1.2 to 115.2 kbps
- Wide operating temperature: -40 to +85 °C
- Rugged IP30 metal panel mount case
- UL C1/D2
- 10-48 VDC power (external power supply required, sold separately)

Model BB-485DRCI-PH is a premium heavy industrial RS-232 to RS-422/485 isolated converter. Designed for rugged industrial environments, it has been put through some of the most exacting compliance tests in the industry. Meeting the requirements of IEC 61850-3 and IEEE 1613, it is suitable for installation in electrical substations. These specifications are more stringent than the NEMA TS1/TS2 requirements for transportation applications.

Powerful isolation on both data ports protects your equipment and data from damaging ground loops and surges. Additional isolation on the power supply circuits adds a third degree of protection. An external power supply is required (not included, sold separately).

Packaged in a rugged IP30 metal case, it converts unbalanced, full or half-duplex RS-232 signals to balanced RS-422/485 signals. Featuring Automatic Send Data Control circuitry, it does not require special software control of handshake signals in RS-485 mode. Bit-wise enabled circuitry automatically detects the data rate without setting a DIP switch.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
BB-485DRCI-PH	Heavy Industrial RS-232 to RS-422/485 Isolated Converter

ACCESSORIES – sold separately

BB-MDR-40-24 – Power Supply, 24VDC, 1.7 A output power, DIN rail mount

BB-TBKT1 – Replacement Terminal Block - 2-position, 5.08mm, 8A, 300V

BB-TBKT2 – Replacement Terminal Block - 5-position, 5.08mm, 8A, 300V

All product specifications are subject to change without notice.
BB-485DRCI-PH_4020ds

ADVANTECH

Advantech B+B SmartWorx, 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 1 (800)346-3119/Toll Free | orders@advantech-bb.com | support@advantech-bb.com

Heavy Industrial RS-232 to RS-422/485 Isolated Converter

Model BB-485DRCI-PH



SPECIFICATIONS

SERIAL TECHNOLOGY	
RS-232	TD, RD, GND
RS-422	TDA(-), TDB(+), RDA(-), RDB(+)
RS-485 4-Wire	TDA(-), TDB(+), RDA(-), RDB(+)
RS-485 2-Wire	Data A(-), Data B(+)
RS-232 Connector	DB9 Female (DCE)
RS-422/485 Connector	5-position, removable terminal block
Data Rate	1.2 to 115.2 Kbps
Isolation	2 kV RMS, 1 minute
Surge Protection	600W peak power dissipation. Clamping time <1 picosecond
Industrial Bus	Modbus ASCII / RTU
Bias	Built-in, switchable 1.2KΩ XMT/RCV
Termination	Built-in, switchable 120Ω
POWER	
Source	External power source required (not included, sold separately)
Power Connector	2-position removable terminal block
Input Voltage	10 to 48 VDC (56 VDC, maximum)
Power Consumption	0.5 W, typical (1.9 W with termination)

TERMINAL BLOCKS	
Wire Size Accepted	28 to 12 AWG, copper wire only
Pitch	5.08 mm
Insulation Resistance	≥500 MΩ @ 500 VDC
Maximum Torque	5 Kg / cm
INDICATORS	
Power	Red LED
TD / RD (Each Port)	Green LED
MECHANICAL	
Dimensions	132.4 x 92.9 x 33.0 mm (5.2 x 3.7 x 1.3 in)
Enclosure	IP30 metal, panel mount
Weight	208.65 gm (0.46 lb)
MEANTIME BETWEEN FAILURES (MTBF)	
MTBF	163611 hours
MTBF Calc. Method	Parts Count Reliability Prediction
ENVIRONMENTAL	
Operating Temperature	-40 to +85 °C (-40 to +176 °F)
Storage Temperature	-40 to +85 °C (-40 to +176 °F)
Operating Humidity	0 to 95%, non-condensing
REGULATORY	
Approvals	FCC, CE UL C1/D2 (IEC 61850-3, IEEE 1613)
CE - Directives	2004/108/EC – Electromagnetic Compatibility Directive 2011/65/EU amended by (EU) 2015/863 Reduction of Hazardous Substances (RoHS)
CE - Approvals	EN 55011 + AC – Information Technology Equipment – Class A RF Emissions EN 61000-6-2 – Generic Immunity Standard for (Heavy) Industrial Environments

MECHANICAL DIAGRAM

