## PCI Express Low Profile Serial Card

Model DSLP-PCIF-100





## **PRODUCT FEATURES**

- Supports serial data transfer rates to 230.4 kbps
- Built-in 16C950 compatible UART
- 128-byte deep Transmit/Receive FIFOs
- · 15V ESD protection on all signal pins
- Compliant with PCI Express Base Specification 1.1

Model DSLP-PCIE-100, RS-232 serial PCI Express Card, meets PCI Express Base Specifications V1.1. It can be installed in virtually any available PC system and is compatible with all major operating systems. Users do not need to set jumpers to configure I/O addresses and IRQ locations.

The board also supports 5VDC or 12VDC of power from each serial port pins 1, 4, 8 or 9. This can be configured via jumpers on the board. If this power is not required, then normal control signals are available. The default configuration is with the jumpers set to disable the power on these pins.

- Supports x1, x2, x4, x8, x16 (lane) PCI Express Bus connector keys
- Supports 2 x UART serial ports
- Optional RS-232 signal or power output to serial device
- Provides 5VDC or 12VDC power output via pins 1, 4, 8, 9
- Plug-n-play, I/O address and IRQ assigned by BIOS
- Support Windows XP/Vista/7, Linux

## **ORDERING INFORMATION**

MODEL NUMBER	DESCRIPTION
DSLP-PCIE-100	2-port Serial RS-232 to DB9, Low Profile, PCI Express Board

## **SPECIFICATIONS**

SERIAL TECHNOLOGY	
Data Transfer Rate	Up to 230.4 kbps
Interface	RS-232
Ports/Connectors	(2) DB9 serial fan out cable; requires 1 PC bracket slot
Machine Compatibility	Low profile systems, standard height configuration with low profile orb installed
O/S Support	Windows XP/Vista/7 (32/64), Linux One available PCI Express slot
ENVIRONMENTAL	
Operating Temperature	-30 to 75°C (-30 to 167 °F)
Storage Temperature	-40 to 85°C (-40 to 185 °F)
Ambient Relative Humidity	5 to 95% Non-condensing
APPROVALS / CERTIFICATIONS	
Certifications	CE, FCC, Compliant with PCI Express Base Specifications 1.1



