RS-232 Universal Data Splitter

Model BB-232UDS





Model BB-232UDS, universal serial data splitter, can be connected so that any two RS-232 devices can connect to any one RS-232 device. For example, two computers can share the same modem or serial printer at the same time and each can remain connected at all times. The other pins must be programmed for proper direction of data flow.

Model BB-232UDS can function as either an modem data splitter or a printer data splitter. It allows you to switch select which lines are OR'd together and which lines are passed straight through. This unit is self-powered from the RS-232 line and can be left permanently installed.

PRODUCT FEATURES

- Share your printer or modems
- Use as a modem or printer data splitter
- Program data flow via DIP switch

ORDERING INFORMATION

MODEL NUMBER	CONNECTOR	MAIN CONNECTOR	CONNECTOR
BB-232UDS	DB25 Female	DB25 Male	DB25 Female

ACCESSORIES - sold separately 232AMF5 - DB25 Male to DB25 Female, 1.8 m (6 ft.)

SPECIFICATIONS			
SERIAL TECHNOLOGY			
RS-232			
Connectors	DB25 female DB25 male DB25 female		
Pins Supported	Pins 1 through 8, 20. (Pins 1 and 7 connected between all 3 connectors.) (Other pins programmable for data flow direction.)		
Installation	In-line		
ISOLATION			
	2,000 VDC		
POWER			
Power	Port-powered		
Source	RS-232 handshake lines		
MECHANICAL			
Weight	176.9 gm (0.39 lb)		
MTBF	895,576		
MTBF Calc. Method	Parts Count Reliability Prediction		
ENVIRONMENTAL			
Operating Temperature	0 to +70 °C (+32 to +158 °F)		
Storage Temperature	-40 to +85 °C (-40 to +185 °F)		
Operating Humidity	ating Humidity 0 to 95% Non-Condensing		
APPROVALS/CERTIFICATIONS			
2011/65/EU	Reduction of Hazardous Substances Directive (RoHS)		
2012/19/EU	Waste Electrical and Electronic Equipment (WEEE)		



Advantech B+B SmartWorx, 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 1 (800)346-3119/Toll Free | orders@advantech-bb.com | support@advantech-bb.com