

GUC232A

USB to Serial RS-232 Adapter



USB to Serial Adapter (RS-232)

The USB to Serial RS-232 Adapter provides one RS-232 Serial (DB-9 male) connector via one standard USB port at a data transfer rate of up to 230Kbps. You can instantly enjoy connectivity with modem, PDA, POS, or other serial devices on your PC or Mac without the hassle of opening your computer case. It provides a quick, simple, and cost-effective solution and is ideal for various communication and automation applications. This makes the USB interface transparent to serial peripherals, allowing them to easily interface with USB computers and eliminates the setup hassle found with traditional serial port connections. This device also supports energy saving suspend and resume operations.

[Declaration of Conformity](#)

- Add one serial port to your PC or Mac via USB connector
- Converts older serial devices to USB connection
- USB 1.1 and USB 2.0 compatible
- 16" cable length
- LED status light for data transfer monitoring
- Supports the RS-232 Serial interface
- Supports automatic handshake mode
- Up to 230Kbps data transfer rate
- Supports remote wakeup and power management
- Provides a 96 byte buffer for each upstream and downstream data transfer
- Easy Installation
- No IRQ required



Requirements

- **For PC Users**
- Windows® 10, Windows® 8.1, Windows® 8, Windows® 7, Windows Vista® , Windows XP®
- Available USB port
-
- **For Mac Users**
- Mac OS X 10.3.9 through 10.9
- Available USB port

Package Contents

- GUC232A USB to Serial adapter cable
- Installation CD
- User Manual
- Warranty/Registration Card

Specifications

Function	GUC232A	Dimensions	GUC232A
Housing		POP Information	
Case	Plastic	10" Peg Hook	5
Power Consumption	90mA	6" Peg Hook	3
LEDs		Unit Dimensions	
On Line	1	Width	1.3" (3.3cm)
Operating Temperature	41 to 104 degree Fahrenheit	Height	.6" (1.6cm)
Storage Temperature	-4 to 140 degree Fahrenheit	Length	16.6" (42.2cm)
USB Specification	USB 1.1 compliant	Unit Package Dimensions	
Transfer Rate	Up to 230Kbps	Width	4.9" (12.5cm)
Humidity	20-80% RH, (Non Condensing)	Height	6.2" (15.7m)
Cable Length	14 in. (40.64 cm.)	Depth	1.6" (4.1cm)
Power Connections	Bus powered	Master Carton	
International - Languages	English	Width	10.9" (27.6cm)
		Height	8.1" (20.6cm)
		Depth	15.5" (39.4cm)
		Master Carton Qty.	24
		Weight	
		Master Carton Wt.	7.9lbs (3.6kg)
		Unit Pack Wt.	.30 lbs (.14kg)
		Unit Wt.	.10lbs (.05kg)