

Door Open/Close Sensor Cable

Model BB-WCHMS

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



KEY FEATURES

- + Contact Size: 33.6 x 13.5 x 7.5 mm (1.32 x 0.53 x 0.3 in)
- + Standard Magnet Size: 33.6 x 13.5 x 7.5 mm (1.32 x 0.53 x 0.3 in)
- + Standard Gap: 21.0 mm (0.83 in)
- + 305 mm (12 in) AWG leads standard
- + Includes: (4) round head screws, 1-72 thread size, 3/8 inch length

OVERVIEW

The flush mount sensor saves space while providing a non-contact way to indicate door open/closed status. The sensor works side, top, or bottom mounted as long as the two pieces are within 0.75" of each other with the door closed.

ORDERING INFORMATION

MODEL NO.	DESCRIPTION	LEAD LENGTH	COLOR
BB-WCHMS	Door Open/Close Sensor Cable	~305mm (12 in)	White

DOOR CONTACT SPECIFICATIONS


PN#	GAP (mm/in)	LOOP Open/Closed	REED FORM	MAX. CONTACT RATING (W)	MAX. INITIAL CONTACT RESISTANCE (mΩ)	AX> SWITCHING VOLTAGE (V)	MAX> SWITCHING CURRENT (A)	COMPLIANCES
FM-102	21.0 mm (0.83 in)	Closed	Normally Open	10	100	AC11 0/ DC110	0.5	CE, RoHS, cUL US Listed

SCHEMATIC

COMN	PIN		PIN	CONN
J1	1	White	1	J2
J1	2	White	2	J2

MECHANICAL DRAWING

Units - mm



All product specifications are subject to change without notice.
BB-WCHMS_3018d